

D型ベンチレーター風量性能表 (m³/min) ※SD型(40メッシュ網付)の場合、約半分となります。

型式	温度差 (°C)	Δt=3°C						Δt=5°C						Δt=10°C						Δt=15°C					
	設置高 (m)	5	10	15	20	25	30	5	10	15	20	25	30	5	10	15	20	25	30	5	10	15	20	25	30
(S)D-150	外気 風速 (m/s)																								
	1	0.7	1.0	1.2	1.3	1.5	1.6	0.9	1.2	1.5	1.7	1.9	2.0	1.2	1.7	2.0	2.3	2.6	2.8	1.5	2.0	2.5	2.8	3.2	3.5
	2	1.0	1.2	1.3	1.5	1.6	1.7	1.1	1.4	1.6	1.8	2.0	2.1	1.4	1.8	2.1	2.4	2.7	2.9	1.6	2.1	2.5	2.9	3.2	3.5
	3	1.3	1.5	1.6	1.7	1.8	1.9	1.4	1.6	1.8	2.0	2.2	2.3	1.6	2.0	2.3	2.6	2.8	3.0	1.8	2.3	2.7	3.0	3.3	3.6
	4	1.7	1.8	1.9	2.0	2.1	2.2	1.7	1.9	2.1	2.2	2.4	2.5	1.9	2.2	2.5	2.8	3.0	3.2	2.1	2.5	2.9	3.2	3.5	3.8
(S)D-180	5	2.0	2.1	2.2	2.3	2.4	2.5	2.1	2.2	2.4	2.5	2.6	2.8	2.2	2.5	2.8	3.0	3.2	3.4	2.4	2.8	3.1	3.4	3.7	3.9
	1	1.1	1.4	1.7	1.9	2.1	2.3	1.3	1.7	2.1	2.4	2.7	2.9	1.7	2.4	2.9	3.3	3.7	4.1	2.1	2.9	3.5	4.1	4.5	5.0
	2	1.4	1.7	1.9	2.1	2.3	2.5	1.6	2.0	2.3	2.6	2.8	3.1	2.0	2.6	3.1	3.5	3.9	4.2	2.3	3.1	3.7	4.2	4.6	5.1
	3	1.9	2.1	2.3	2.5	2.6	2.8	2.0	2.3	2.6	2.9	3.1	3.3	2.3	2.9	3.3	3.7	4.0	4.4	2.6	3.3	3.9	4.4	4.8	5.2
	4	2.4	2.6	2.7	2.9	3.0	3.1	2.5	2.8	3.0	3.2	3.4	3.6	2.8	3.2	3.6	4.0	4.3	4.6	3.0	3.6	4.1	4.6	5.0	5.4
(S)D-210	5	2.9	3.1	3.2	3.3	3.4	3.6	3.0	3.2	3.4	3.6	3.8	4.0	3.2	3.6	4.0	4.3	4.6	4.9	3.4	4.0	4.5	4.9	5.3	5.7
	1	1.4	1.9	2.3	2.6	2.9	3.1	1.8	2.4	2.9	3.3	3.6	4.0	2.4	3.3	4.0	4.6	5.1	5.5	2.9	4.0	4.8	5.5	6.2	6.8
	2	2.0	2.3	2.6	2.9	3.1	3.4	2.2	2.7	3.1	3.5	3.9	4.2	2.7	3.5	4.2	4.7	5.2	5.7	3.1	4.2	5.0	5.7	6.3	6.9
	3	2.6	2.9	3.1	3.3	3.6	3.8	2.8	3.2	3.6	3.9	4.2	4.5	3.2	3.9	4.5	5.0	5.5	5.9	3.6	4.5	5.3	5.9	6.6	7.1
	4	3.3	3.5	3.7	3.9	4.1	4.3	3.4	3.8	4.1	4.4	4.7	4.9	3.8	4.4	4.9	5.4	5.9	6.3	4.1	4.9	5.6	6.3	6.9	7.4
(S)D-250	5	4.0	4.2	4.3	4.5	4.7	4.8	4.1	4.4	4.7	4.9	5.2	5.4	4.4	4.9	5.4	5.9	6.3	6.7	4.7	5.4	6.1	6.7	7.2	7.7
	1	1.9	2.5	3.0	3.4	3.7	4.1	2.3	3.1	3.7	4.3	4.7	5.2	3.1	4.3	5.2	5.9	6.6	7.2	3.7	5.2	6.3	7.2	8.1	8.8
	2	2.5	3.0	3.4	3.8	4.1	4.4	2.9	3.5	4.1	4.6	5.0	5.4	3.5	4.6	5.4	6.2	6.8	7.4	4.1	5.4	6.5	7.4	8.3	9.0
	3	3.4	3.7	4.1	4.4	4.7	4.9	3.6	4.2	4.7	5.1	5.5	5.9	4.2	5.1	5.9	6.6	7.2	7.8	4.7	5.9	6.9	7.8	8.6	9.3
	4	4.3	4.6	4.8	5.1	5.3	5.6	4.5	4.9	5.3	5.7	6.1	6.4	4.9	5.7	6.4	7.1	7.7	8.2	5.3	6.4	7.4	8.2	9.0	9.6
(S)D-250	5	5.2	5.4	5.7	5.9	6.1	6.3	5.4	5.8	6.1	6.5	6.8	7.1	5.8	6.5	7.1	7.7	8.2	8.7	6.1	7.1	7.9	8.7	9.4	10.1

※屋根に設置する場合の参考風量となります。ダクト接続で使用する機種は表には当てはまりません。