


番号	部 品 名	材 質 又は 規 格	数量
1	ドアフレーム	ガルバリウム鋼板 t=1.6	1
2	網入り型板ガラス	t=6.8 (580×580)	1
3	ドーム	アクリル樹脂	1
4	ベース	ガルバリウム鋼板 t=1.6	1
5	ボディ	ガルバリウム鋼板 t=1.6	1
6	ガススプリング	窒素ガス封入式	2
7	蝶 番	SUS304 HOT t=3.0	2
8	取っ手	H-17-SUS-5	1
9	クリップパッチン錠	PP-22-SUS	1

採光面積 0.25 m²

注記）南京錠等、鍵は別途とします。

殿		殿		特記事項		No. 年 月 日		訂 正 追 記 事 項		記入者		単位		m/m		日付		'15・10・01		工 事 名 称			
御受領印		御受領印				A						A		1/10 1/2		A		1/20 1/4		図 面 名 称		HTQ-600GDA-GL (鍵穴付)	
						A						A				承認				 三和工業株式会社		図 面 番 号 20 - 06	
						A						設計											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											
						A						A											